

GET8 Series PETG Shrink Film Ink

[Product description]

GET8 series ink is a gravure reverse print alcohol solvent based PETG shrink film ink; it is used for PETG shrink film labels for glass bottle, soft drink bottle and canned food

[Product features]

- ❖ High colour strength, excellent colour reproduction
- ❖ Good printing performance and anti-blocking resistance

[Printing substrate]

Normal PETG heat shrink film

[Dilution]

Drying speed Solvent	Fast	Medium	Slow
Ethyl acetate	60	40	20
n-propyl acetate	20	20	20
n-butyl acetate	-	20	40
IPA	20	20	20

[Printing viscosity]

Printing viscosity varies with printing speed and printing condition

Usually viscosity cup (Sheen2# or TOYO3#) 15-25 sec/ 25 °C

[Precaution]

❖ Actual ink dilution depends on printing speed and other factors, if excess dilution dried ink film could be too thin and scratch and rub resistance could be reduced. Typical dilution ratio is 0.2-0.5:1

Version: BV-QESR-YMTA-TDS-010-B/0

Release date: 2017.05.04



❖ If light fastness is required, please use ink with better light fastness performance

[Disclaimer]

This specification is in accordance with the actual production and test results, whether the product could meet your process requirements depends on application conditions and printed material. We recommend the users to assess if the product can meet all their requirements before production. Since we cannot predict or control your printing condition, the product performance cannot be guaranteed all sales are subjected to the standard terms and conditions of the sales control division.

Version: BV-QESR-YMTA-TDS-010-B/0

Release date: 2017.05.04