

Paper Solvent

[Product introduction]

- This product can meet the performance requirements of different customers for different packaging and printing accessories.
- ❖ It has printing machine washing water, leather washing water, blister oil quick drying diluent, coating diluent, disinfectant and other characteristic products to meet the different characteristic needs of customers.

Specifications

- ❖ Appearance: Clear transparent liquid, no mechanical impurities
- **♦** Chromaticity: ≤20 (Pt-Co)
- ❖ Moisture content: 0.7-1

[Main components]

- Alcohols
- Benzene
- Esters
- Alkanes
- Water
- Additives

[Applicable machine]

- Printing line, local anilox roller oiler, roller oiler.
- ❖ It is used for printing machine washing water, UV oil, water-based coating and blister oil diluent.

(Packing and storage)

- Packing materials and packing specifications: iron bucket, net weight 13kg, 15kg, 160kg
- ❖ Storage conditions and shelf life: Sealed storage, 12 months.

[Precautions]

* This product is extremely flammable and dangerous. Please avoid direct sunlight,



keep away from fire and no smoking.

- ❖ Please pay attention to ventilation during construction to ensure air circulation.
- ❖ Please avoid direct contact with skin. Forbidden entry.
- ❖ If you accidentally enter your eyes or mouth, please rinse with plenty of water immediately and seek medical advice as soon as possible.

[Disclaimer]

This specification is in accordance with the actual production and test results, whether the product could meet your process requirements depends on application conditions and printed material. We recommend the users to assess if the product can meet all their requirements before production. Since we cannot predict or control your printing condition, the product performance cannot be guaranteed all sales are subjected to the standard terms and conditions of the sales control division.

Version: BV-QESR-YMTA-TDS-485-B/0 Release date: 2021.06.10